













安装说明


Assassin King 120 mini 系列

www.thermalright.com


配件清单

AMD AM4




移除AMD原装散热支架, 拆下背板, 使用背板上的4个M4螺丝固定背板




将AMD原装散热支架, 按照背板上的位置, 使用M4螺丝固定到背板

涂好导热膏, 然后安装好散热器, 再固定风扇

INTEL LG4115X




将LG4115X背板安装在CPU底座背面, 然后正面固定背板, 支架, 再拆掉背板上的M4支架




将LG4115X螺钉拧到主板, 然后设置支架, 再拆掉固定架 INTEL 支架

涂好导热膏, 然后安装好散热器, 再固定风扇

INTEL LG4200X




将LG4200X螺钉拧到主板, 然后设置支架, 再拆掉固定架 INTEL 支架




将LG4200X螺钉拧到主板, 然后设置支架, 再拆掉固定架 INTEL 支架

涂好导热膏, 然后安装好散热器, 再固定风扇


风扇接线




如果风扇有LED灯, 请将RGB灯线 (5V / GND) / 4pin (12V) 插入主板上的RGB灯线接口或者5pin灯线接口, 如果没有, 请勿连接。



将风扇线材插入主板CPU_FAN1/2/3/4插座

















INSTALLATION GUIDE


Assassin King 120 mini Series

www.thermalright.com


parts list

AMD AM4




Remove AMD original heat sink, then keep the backplate over the brackets using the AM4 screws.




Place the fan onto the backplate, then keep the backplate over the fan and the LG4115X bracket until then tightening the fan to secure.

Apply a thin layer of thermal grease, and then secure backplate.

INTEL LG4115X




Put the fan onto the backplate, then keep the backplate over the standoff and the LG4115X bracket until then tightening the fan to secure.




Place the fan onto the backplate, then keep the backplate over the standoff and the LG4115X bracket until then tightening the fan to secure.

Apply a thin layer of thermal grease, and then secure backplate.

INTEL LG4200X




Put the fan onto the backplate, then keep the backplate over the brackets and then tighten with fan.




Place the fan onto the backplate, then keep the backplate over the brackets and then tighten with fan.

Apply a thin layer of thermal grease, and then secure backplate.

Fan wiring



If the fan has LED light effect, please insert RGB lamp effect 3-pin (5V) / 4-pin (12V) into the motherboard corresponding connector, and connect multiple fans in series.



Insert the fan 4-pin connector into the motherboard CPU fan-pin socket

